

**WE DESIGN
WE MAKE**
Dai Shin Enterprise Co

DRUM FANS

D-TANK SERIES

D-TANK SERIES is our Economy Drum Fan. The series is designed to be at lower level compare to our TANK SERIES. The whole fans are metal build structure, Strong & Durable motors create big airflow at low power consumption range from 1/4HP to 1HP.

- High Velocity stand Fan, Size from 24inches to 30inches
- Direct drive & Close motor or Open motor
- Metal blades with 3 impellers
- Two rubber wheels help moving easier and faster
- Coated steel guards, housing to protect from moving blades
- Energy efficiency & Strong performance
- UL/ETL/CE applicable



MODEL NO.	BLADE DIA	VOTAGE	AIR SPEED (m/min)	AIR FLOW (m ³ /min)	APPERAGE	POWER (W)	RPM	DIMENSION L * W * H (mm)	N.W
DTANK-2460	24" (60cm)	100V, 50/60Hz	217/233	214/235	1.52/1.88	138/182	906/1000	740x315x720	17.1
		240V/50Hz	210	207	0.62	150	895		
DTANK-3076	30" (76cm)	100V, 50/60Hz	511/592	232/269	3.62/3.59	271/345	945/1105	925x335x870	20.4
		230V/50Hz	357	255	1.36	256	900		

KIN SERIES

KIN SERIES is our premium quality fan, the fans we design to supply fresh air or exhaust polluted air. It can be used with soft airduct. The whole fans are metal build structure, Strong & Durable motors create big airflow at low power consumption.

Specifications:

- Size: from 7inches to 24inches
- Direct drive & Close motor
- blades with 6 impellers
- Coated steel guards, housing to protect from moving blades
- Plastic handle, easy to carry
- Energy efficiency & Strong performance
- UL/ETL/CE applicable



MODEL NO.	SIZE	VOTAGE	AIR SPEED (m/min)	AIR FLOW (m ³ /min)	APPERAGE	POWER (W)	RPM	DIMENSION L * W * H (mm)	N.W
KIN-200	20cm	100V, 50/60Hz	397/467	25/29	1.14/1.24	95/125	2890/3400	258*335*310	9.2
		110V/60Hz	469	29	1.14	126	3430		
		120V/60Hz	473	30	1.17	137	3460		
		220V, 50/60Hz	397/469	25/29	0.65/0.61	107/135	2905/3430		
		230V/50Hz	395	25	0.49	101	2890		
		240V/50Hz	397	25	0.52	105	2900		
KIN-300	30cm	100V, 50/60Hz	435/507	67/77	3.28/4.42	294/442	2900/3380	341*355*380	12.9
		110V/60Hz	510	76	3.4	380	3400		
		120V/60Hz	515	77	3.42	400	3430		
		220V, 50/60Hz	431/509	65/78	1.5/2.01	296/444	2890/3390		
		230V/50Hz	432	66	1.2	258	2880		
		240V/50Hz	432	66	1.23	278	2880		
KIN-500	50cm	100V, 50/60Hz	312/362	224/260	4.2/5.0	330/480	1435/1665	620*480*695	23.2
		110V/60Hz	370	265	4.13	440	1700		
		120V/60Hz	374	267	4.17	480	1720		
		220V/50Hz	315	226	2.12	340	1450		
		230V/50Hz	312	224	1.34	310	1435		
		240V/50Hz	314	226	1.39	330	1445		
KIN-2050	20" (50cm)	100V, 50/60Hz	600/720	124/145	4.52/6.16	416/610	1420/1620	645*480*750	23.2
		110V/60Hz	403	79	4.84	530	1660		
		120V/60Hz	408	80	4.64	570	1680		
		220V/50Hz	356	70	1.98	390	1430		
		230V/50Hz	348	68	1.58	365	1415		
		240V/50Hz	354	70	1.6	375	1420		
KIN-2460	24" (60cm)	110V/60Hz	504	143	7.37	790	1700	730*480*840	30.6
		120V/60Hz	509	144	7.11	823	1715		
		220V/50Hz	429	122	3.53	580	1445		
		230V/50Hz	421	119	2.4	545	1420		
		240V/50Hz	423	120	2.42	560	1425		

